



according to Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 14.05.2019

Revision number 1.2

Version date: 14.05.2019

1 Identification of the substance/mixture and of the company/undertaking
 1.1 Product identifier
 Product name: Lederölspray

- Product code: 321586
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses of the substance or mixture Aerosol

1.3 Details of the supplier of the safety data sheet Albert Kerbl GmbH Felizenzell 9 D-84428 Buchbach www.kerbl.com Tel.: 0049-(0)8086-933-100

• Responsible Department: Albert Kerbl GmbH Tel.: 0049-(0)8086-933-104 E-Mail: bm@kerbl.com

E-Mail: info@kerbl.com

Emergency telephone number: Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen c/o HELIOS Klinikum Erfurt Nordhäuser Straße 74 Tel.: (03 61) 73 07 30 - Fax: (03 61) 7 30 73 17 E-Mail: ggiz@ggiz-erfurt.de - Internet: www.ggiz-erfurt.de

2 Hazards identification

2.1 <u>Classification of the substance or mixture</u>

Classification according to Regulation (EC) Nr. 1272/2008 Aerosol: Aerosol 1 (H222, H229) Repeated exposure may cause skin dryness or cracking (EUH066)

2.2 Label elements

Label elements according to Regulation (EC) Nr. 1272/2008 (CLP/GHS) Hazard pictograms





Regulation (EC) Nr. 1907/2006 (REACH)

 Print date: 14.05.2019
 Revision number 1.2
 Version date: 14.05.2019

 Product name: Lederölspray
 Product code: 321586

Hazard statements

H222 - Extremely flammable aerosol.

H229 - Pressurized container: May burst if heated.

EUH066 - Repeated exposure may cause skin dryness or cracking.

Precautionary statements

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P410+P412 - Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.

2.3 Other hazards

• The mixture does not meet the criteria for PBT or vPvB.

3 Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients:

CAS: 68551-19-9 EC-Nr. 927-285-2 Reg.nr. 01-2119480162-4	Hydrocarbons, C11-C14 Asp. Tox. 1, H304; EUH066 I5	30-60 %
CAS: 106-97-8 EC-Nr. 203-448-7 Index-Nr. 601-004-00-0	Butane Flam. Gas 1: H220; Press. Gas: H280	5-20 %
CAS: 75-28-5 EC-Nr. 200-857-2 Index-Nr. 601-004-00-0	Isobutane Flam. Gas 1: H220; Press. Gas: H280	5-20 %
CAS: 74-98-6 EC-Nr. 200-827-9 Index-Nr. 601-003-00-5	Propane Flam. Gas 1: H220; Press. Gas: H280	5-20 %
Additional information:		

The wording of the listed risk phrases and hazard statements refer to section 16.

4 First aid measures

4.1 Description of first aid measures

· General information:

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

· Inhalation:

Move to fresh air. If symptoms persist, call a physician.

· Skin contact:

Remove immediately any soiled or splashed garment. Rinse abundantly in the water and in the soap. Clean clothes separately before reusing them. Consult a doctor in case of persistent pain.



Print date: 14.05.2019

Safety Data Sheet

Regulation (EC) Nr. 1907/2006 (REACH)

Revision number 1.2

Version date: 14.05.2019

Product name: Lederölsprav

Product code: 321586

· Eye contact:

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open. If there is any redness, pain or visual impairment, consult an ophthalmologist. Indestion:

Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Do not induce vomiting. Get medical advice/attention if you feel unwell.

- 4.2 Most important symptoms and effects, both acute and delayed Inhalation of spray mist is irritating to the upper airways.
- 4.3 Indication of any immediate medical attention and special treatment needed None

5 Firefighting measures

5.1 Extinguishing media

Suitable methods of extinction - In the event of a fire, use: sprayed water or water mist, foam, multipurpose ABC powder, BC powder, carbon dioxide (CO2) Unsuitable methods of extinction - In the event of a fire, do not use: water jet

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health. Do not breathe in smoke. In the event of a fire, the following may be formed: carbon monoxide (CO), carbon dioxide (CO2)

5.3 Advice for firefighters

Special protective equipment: Wear self-contained breathing apparatus. **Further information**

Cool endangered containers with water spray jet. Dispose fire residues and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected people away. Keep people away and stay on the upwind side. Keep ignition sources away. No smoking. Consult the safety measures listed under headings 7 and 8. 6.2 Environmental precautions:
 - Avoid unnecessary release to the environment. Prevent any material from entering drains or waterways. In case of entry into waterways, soil or drains, inform the responsible authorities.
- 6.3 Methods and material for containment and cleaning up: Collect spillage. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ensure adequate ventilation.

6.4 Reference to other sections

Information regarding safe handling see chapter 7. Information regarding personal protection see chapter 8. Information regarding disposal see chapter 13.



Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 14.05.2019

Revision number 1.2

Version date: 14.05.2019

Product name: Lederölspray

Product code: 321586

7 Handling and storage

7.1 Precautions for safe handling

Ensure that there is adequate ventilation, especially in confined areas.

- Open and handle container with care.
- Fire prevention:

Keep ignition sources away - Do not smoke. Take precautionary measures against static discharges. Pressurized container. Protect from sunlight and temperatures above 50 ° C (eg by Electric lights). Do not open by force or burn even after use. Do not spray in flames or on hot surfaces.

7.2 Conditions for safe storage, including any incompatibilities Storage

· Requirements for storage rooms and vessels: Store in a cool place. Official regulations on storing pressurized containers must be observed. Store away from oxidizing agents. Further information about storage conditions: Store in tightly closed containers in a cool, dry place. Protect from heat and direct sunlight. Ensure adequate ventilation. Recommended storage temperature: 5-40°C Storage class: 2B, Aerosols.

7.3 Specific end use(s) Keep out of reach of children.

8 Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits		Exposure			
· · ·	Country	limit	ml/m³	mg/m³	Remarks
68551-19-9 Hydro-	D, TRGS 900	AGW		300	2(II); AGS
carbons C11-C14	4				RCP-Gruppe
106-97-8 Butane	D, TRGS 900	AGW	1000	2400	4(II);DFG
	UK, WEL	TWA	600	1450	8 ĥ
		STEL	750	1810	15 min
	F, INRS	VME	800	1900	8 h
74-98-6 Propane	D, TRGS 900	AGW	1000	1800	4(II);DFG
-	UK, WEL	TWA	1000	1800	8 ĥ
75-28-5 Isobutane	D, TRGS 900	AGW	1000	2400	4(II);DFG

8.2 Exposure controls / Personal protection

Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area. Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.



<u>יח</u>

roduct name: Lederöls		
	spray	Product code: 321586
handling, wear safet event of high danger accordance with star Individuals wearing o	yes. Use eye protectors designed to pr y goggles with protective sides accorda ; protect the face with a face shield. W ndard EN166. Prescription glasses are contact lenses should wear prescriptior t vapours. Provide eyewash stations in	ance with standard EN166. In the hen spraying, wear a face shield in not considered as protection. a glasses during work where they ma
Hand protection		
Wear suitable protect protective gloves that Gloves must be select Protective gloves need other chemical produ	tive gloves in the event of prolonged or t are resistant to chemical agents in ac cted according to the application and d ed to be selected according to their suit acts that may be handled, necessary ph el of dexterity required. hmended :	cordance with standard EN374. uration of use at the workstation. ability for the workstation in question
 Nitrile rubber (butad PVC (polyvinyl chlor Butyl Rubber (Isobu Recommended properties 	itylene-isoprene copolymer)	BR))
Work clothing worn b	er than of the hands) by personnel shall be laundered regula it have been soiled must be washed.	rly. After contact with the product, all
Respiratory protection		
	t ventilation, wear respiratory protective	e equipment with filter.
Thermal hazards		
	er: May burst if heated.	
Exposure controls re No data available.	egarding environmental protection	

- · pH:
- · Change of state Melting point/range: **Boiling point/range:**
- · Flash point:
- · Flammability (solid, gas):
- · Ignition temperature:
- · Thermal decomposition:

not relevant -42,1/-11,7/-0,5 °C (Propane/Isobutane/Butane) -104/-83/-60 °C (Propane/Isobutane/Butane) not applicable 450/460/365 °C (Propane/Isobutane/Butane) not relevant

not determined



Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 14.05.2019 Revision number 1.2 Version date: 14.05.2019 Product name: Lederölspray Product code: 321586 · Autoinflammability: not self-flammable · Explosion hazard: Pressurised container: May burst if heated. · Explosion limits: 1,7/1,5/1,4 Vol.-% (Propane/Isobutane/Butane) Lower: 10,8/9,4/9,4 Vol.-% (Propane/Isobutane/Butane) Upper: Vapour pressure at 20 °C: 8,33/3,02/2,08 bar (Propane/Isobutane/Butane) · Density: not determined · Bulk density not determined · Vapour density not determined · Evaporation rate not determined · Solubility / miscibility Water: insoluble · Partition coefficient (n-Octanol/Water): not determined · Viscosity: not determined not determined Oxidising properties 9.2 Other information No data available.

10 Stability and reactivity

- 10.1 Reactivity Heating may cause a fire or explosion.
- **10.2 Chemical stability** This mixture is stable under the recommended handling and storage conditions in section 7.
- **10.3 Possibility of hazardous reactions** No hazardous reactions when stored under the recommended handling and storage conditions.

10.4 Conditions to avoid:

Sunlight. High temperatures. Keep away from sources of ignition.

10.5 Incompatible materials: Reacts with strong oxidants.

10.6 Hazardous decomposition products: None when used as intended.

11 Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

68551-19-9 Hydrocarbons,	C11-C14
--------------------------	---------

Oral	LD-50	>5000 mg/kg (Rat)
Dermal	LD-50	>5000 mg/kg (Rabbit)
Inhalation	LC50	>5000 mg/m³ (Rat)

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.



Regulation (EC) Nr. 1907/2006 (REACH)

Print date: 14.05.2019Revision number 1.2Version date: 14.05.2019Product name: LederölspravProduct code: 321586

Eye damage/irritation:

Based on available data, the classification criteria are not met.

Sensitisation, respiratory or skin:

Repeated exposure may cause skin dryness or cracking.

Carcinogenicity, germ cell mutagenicity, reproductive toxicity (CMR): Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT), single/repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional toxicological information:

Inhalation of concentrated vapors as well as oral intake will lead to anesthesia-like conditions and headache, dizziness, etc. Has a degreasing effect on the skin!

12 Ecological information

12.1 Toxicity

Aquatic Toxicity:

68551-19-9 Hydrocarbons, C11-C14

LC-50 >1000 mg/l (Fish, 96 h)			
LC-50	>1000 mg/l (Algae, 72 h)		
LC-50	>1000 mg/l (Daphnia Magna, 48 h)		
12.2 Persistence and degradability		Readily biodegradable.	
12.3 Bioaccumulative potential		The product is not bioaccumulative.	
12.4 Mobility in so	il	No data available.	
12.5 Results of PBT and vPvB assessment		The mixture does not meet the criteria for PBT or vPvB.	
12.6 Other adverse effects		No data available.	

13 Disposal considerations

13.1 Waste treatment methods

Recommendation:

Must not be disposed together with household garbage. Do not empty into drains. Must be supplied to an authorized hazardous waste incineration plant, after pretreatment, in accordance with regulations for special waste.

European waste catalog

The listed (n) waste number (s) according to the European Waste Catalogue (EWC), are a recommendation. A final decision must be taken in agreement with the regional waste management company.

16 05 04* gases in pressure containers, containing hazardous substances (including halons) **Uncleaned packaging:**

Recommendation: Disposal according to official regulations.



Regulation (ÉC) Nr. 1907/2006 (REACH)

Print date: 14.05.2019Revision number 1.2Version date: 14.05.2019Product name: LederölsprayProduct code: 321586

14 Transport information		
14.1 UN number · ADR/RID, ADN, IMDG, ICAO/IATA	UN1950	
14.2 UN proper shipping name · ADR/RID, ADN IMDG · ICAO/IATA	AEROSOLS AEROSOLS AEROSOLS, flammable	
14.3 Transport hazard class(es) · ADR/RID, ADN, IMDG, ICAO/IATA	2.1	
Classification code · ADR/RID, ADN	5F	
Special Provisions · ADR/RID, ADN · IMDG · ICAO/IATA	190, 327, 344, 625 63, 190, 277, 327, 344, 959 A145, A167, A802	
14.4 Packing group	none	
14.5 Environmental hazards	none	
14.6 Special precautions for user		
EmS	F-D, S-U	
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		
	Not applicable	

Not applicable.

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU-Regulations

None

National Regulations

<u>Germany</u>: Wassergefährdungsklasse (WGK) Water hazard class non-hazardous to water (nwg), Classification according to AwSV

15.2 Chemical safety assessment: No data available



Print date: 14.05.2019

Safety Data Sheet Regulation (EC) Nr. 1907/2006 (REACH)

Revision number 1.2

Version date: 14.05.2019

Product name: Lederölspray

Product code: 321586

16 Other information

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations. The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Revision notes

* Changes since the last version

Abbreviations

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

Title for H and EUH indications (Number and text)

H220 - Extremely flammable gas.

H222 - Extremely flammable aerosol.

H229 - Pressurized container: May burst if heated.

H280 - Contains gas under pressure; may explode if heated.

H304 - May be fatal if swallowed and enters airways.

EUH066 - Repeated exposure may cause skin dryness or cracking

Methods of evaluating information referred to in Article 9 of Regulation (EC) No 1272/2008 for the purpose of classification

Classification based on the components